



ADHESIVE BACKED FLASHING TAPE BY OTHERS

GRIDWORX STARTER J ANCHOR

LOW MODULUS SILICONE W/ OPEN CELL BACKER ROD

1/4" FOAM TAPE PRE-APPLIED TO GRIDWORX L BRACKET

GRIDWORX L BRACKET @ 1/4 POINTS OF STONE PANEL

LOW MODULUS SILICONE APPLIED INTO KERF AT ANCHOR LOCATIONS

1 3/8" STONE PANEL

GRIDWORX L Bracket @ 1/4 POINTS OF STONE PANEL

GRIDWORX HEADER L ANCHOR

WEEP SLOTS @ 24" O.C.

WATERPROOFING MEMBRANE AT FACE OF SHEATHING

GRIDWORX HEADER L ANCHOR

#12 x 2 DUAL TEMPERED SCREW W/ STALGARD FINISH PREP EXTRUSION W/ 0.228" x 1" SLOT - 16" O.C.

FULL BEARING HI-IMPACT RESISTANT PLASTIC SHIMS

PLYWOOD SHEATHING OVER METAL STUDS @ 16" O.C.

#12 x 2 DUAL TEMPERED SCREW W/ STALGARD FINISH PREP EXTRUSION W/ 0.228" x 1" SLOT - 16" O.C.

DETAIL A3

SCALE: 1:2

INTERMEDIATE RAILING DETAIL
38 COMMERCE



Precision Wall Systems, Inc.
1821 Levee Street
Dallas, TX 75207
Phone 214.774.4502
Fax 214.432.5963
www.gridworxwalls.com