



- GYPSUM WALLBORD,
- STEEL STUD WALL,
- STEEL STUD FIRING,
- EXTERIOR SHEATHING,
- CONTINUOUS AIR/VAPOUR BARRIER MEMBRANE,
- RIGID INSULATION BETWEEN "Z" CHANNELS (THICKNESS OF INSULATION DEPENDENT ON REQUIRED R-VALUE),
- 1" AIR SPACE, WITH GRIDWORX ALUMINUM CHANNELS, CALCIUM SILICATE UNITS
- FLASHING MEMBRANE SURFACE ADHERE TO SUBSTRATE
- "Z" CHANNELS TO CONTINUE DOWNWARDS TO SUPPORT SOFFIT
- COMPRESSIBLE BACKER ROD AND SEALANT
- UNOBSTRUCTED WEEP SYSTEM @ 24" O/C
- PREFINISHED METAL DRIP EDGE
- HOHMANN & BARNARD ANCHOR ATTACHED TO "C" CHANNELS TO SUPPORT STONE IN ADDITION TO GRIDWORX CHANNELS
- WOOD BLOCKING
- SPRAY APPLIED FOAM INSULATING AIR SEAL ALL AROUND FRAME
- PREMANUFACTURED THERMALLY BROKEN ALUMINUM WINDOW ASSEMBLY

**CUSTOM SOFFIT
ALUMINUM WINDOW HEAD
3/8" JOINT - STEEL FRAMING
W/ Z CHANNEL**

SCALE: 1:4



Precision Wall Systems, Inc.
1821 Levee Street
Dallas, TX 75207
Phone 214.774.4502
Fax 214.432.5963
www.gridworxwalls.com